Upstream Geothermal Development

Narendra Widjajanto

Netherlands, November 19, 2013

Skyline Building Lt. 11

Jl. MH. Thamrin No. 9, Jakarta Pusat Telp: 021-39833222 Fax: 021-39833230

www.pge.pertamina.com



Overview of Indonesia Geothermal Potential

Overview of Geothermal Cycles

Exploration and Resource Confirmation

Key Factor for Geothermal Development



Overview of Indonesia Geothermal Potential


Overview of Geothermal Cycles

Exploration and Resource Confirmation

Key Factor for Geothermal Development




Indonesia has the highest potential for geothermal energy in the world, which remains largely untapped




Source : Indonesia's Geothermal Reserve and Utilization Status, Compared to Other Countries (PT. Pertamina Geothermal Energy, PIT API XII November 2012)

PERTAMINA
GEOTHERMAL ENERGY

Gol is making a strong push for renewable energy, with plans to significantly increase geothermal power generation






¹ 2025 proposition is assumed to be the same as shown in RUPTL 2020

SOURCE: PGE annual report, Press reports, Team analysis



Geothermal Resources Map of Indonesia





PGE's Working Areas


Concession Area = 14 (MEMR Decree No 2067K/30/MEM/2012 Total Installed Capacity PGE = 402 MW

STATUS: 2013



PGE projects are in different stages of project development





Overview of Indonesia Geothermal Potential


Overview of Geothermal Cycles

Exploration and Resource Confirmation

Key Factor for Geothermal Development



GEOTHERMAL PROCESS





Overview of Indonesia Geothermal Potential

Overview of Geothermal Cycles

Exploration and Resource Confirmation

Key Factor for Geothermal Development



A typical Geothermal Project has 3 Phases Upstream

Approximate figures TYPICAL 50 MW PROJECT **Exploration Development Operation** Opera-**Geology &** Reservoir Desktop Geo-**Feasibility** Delineation Production SGS tions and Geo-& exploration managestudy drilling physics study drilling construction mainchemistry Major **NORC** Commissioning NOID milestones Internal go/no-go milestones MT survey Drill up to 3 Drill 4-7 Regular Construct discovery production operations steam Key wells and injection gathering activities wells systems and piping 6-9 1 3-4 12-15 2-3 0-6 In parallel N/A N/A Up to 15 **Approx** with months duration production (months) drilling \$5k \$30-50k \$300-500k \$15-25m \$300k (If needed) \$25-50m \$10-15m N/A N/A **Approx** cost (\$)

SOURCE: Expert inputs



Exploration & Resource Confirmation Phase

No	Phase	Activites	Potensial Risk
1	 Geology & Geochemistry Geophysics Infrastructure & exploration drilling 	 Prepare exploration program Process project approval for Environment Process local and regional permit for land and forest usage Procurement process and execution Bridges dan roadways preparation Land clearance with locals 	 Geological Hazards (Landslide Subsidence vs "Cut & Fill") Civil Works (Technology & Competency) Uncertainty for various permit approvals
2	Drilling (exploration & production)	 Prepare detailed drilling program Rig Mobilization & Logistics Rig review Dilling process execution 	 Drilling execution risk Geological risk (hard rocks, fracture, permeability) Gas / steam leakages
3	Production Testing	Prepare testing facilitiesHeating up periodFinal testing	 Steam result confirmation delay due to long heating up period. Resource risk leads to steam availability/reinjection well below target

PERTAMINA
GEOTHERMAL ENERGY

02 Desember 2013 Pages 13

Overview of Indonesia Geothermal Potential


Overview of Geothermal Cycles

Exploration and Resource Confirmation

Key Factor for Geothermal Development



Key Barriers For Developing Indonesia's Geothermal Potential




Barriers make it challenge to mobilize significant investments for achieving GoI target

> Page 15 GEOTHERMAL ENERGY

Resource Risk Make it More Challenging To Mobilize Investment


 Uncertainties associated with geothermal field conditions and resource characteristics during the initial stages of field development will cause developers to require a price premium for taking on this risk



SOURCE: ESMAP World Bank Geothermal Handbook 2012



Geothermal Project Cost Structure



- Cost ranges can vary depending a variety of factors such as: depth of the resource, geologic characteristics and temperature
- Upstream Cost less than Dowstream Cost but having the most riskiest part.
- The upstream phases, (drilling phase), can be considered the riskiest parts of geothermal project development.

PERTAMINA
GEOTHERMAL ENERGY

02 Desember 2013 Page 17

Overview of Indonesia Geothermal Potential

Overview of Geothermal Cycles

Exploration and Resource Confirmation

Key Factor for Geothermal Development



Next Steps for Managing Geothermal Barriers

No	Barriers	Explanation	Next Steps
1	Project delayed due to Various Permits uncertainty	 Uncertainty for acquiring apporvals from local and national government agency 	 Project socialization Revised related procedures / regulation to support green energy development especially for geothermal activities
2	Resource and Upstream Risks	 Steam availability below target Difficulties in getting injection wells 	 Expert and technology enhancement Operational excellence Prepare sufficient time to develop geothermal fields properly (5-7 years) Increase risk mitigation in developing upstream projects in parallel Upstream Risk beared by Government



Next Steps for Managing Geothermal Barriers

No	Barriers	Explanation	Next Steps
3	Offtake uncertainty and financial risk	 Adequate pricing for steam and electricity 	 Propose more attractive new tariff to the government to increase certainty in geothermal investment projects Includes environment cost in coal tariff in order gain comparability with geothermal tariff



